



Enclosure 2

(Application No. 10/754,800; Office Action 2, mailed 12/23/2005)

Method of Defense-in-Depth Ultrasound Intrusion Detection

Inventors: Robert H. Roche, Westminster; Vadym Buyalsky, Reisterstown; Vladimir Herman, Montgomery Village, all of Maryland (US).

Assignee: CTRL Systems, Inc., Westminster, MD.

Int. Cl. **G01S 15/00; G01N 29/00.**

U.S. Cl. **367/93; 367/99; 73/628.**

Field of Search **73/570, 584, 592, 625-628; 109/38, 40;**
340/425, 426, 431, 505, 522, 539, 540, 541, 545.3, 552,
554, 568, 573, 683, 825.3, 988; 342/28;
348/163; 367/1, 5, 13, 87, 88, 93, 99.

RELATED REFERENCES CITED

U.S. PATENT DOCUMENTS

4,582,065	4/1986	Adams73/626
4,644,509	2/1987	Kiewit, et al. 367/87
4,677,852	7/1987	Pinyan73/628
4,733,562	3/1988	Saugeon 73/626
4,949,074	8/1990	D'Ambrosia, et al. 340/552
5,231,608	7/1993	Matsui367/93
5,483,224	1/1996	Rankin, et al. 340/539
5,761,155	6/1998	Eccardt, et al.367/99
5,872,516	2/1999	Bonge 340/573
5,912,620	6/1999	Lin 340/554
5,920,521	7/1999	Kromer, et al. 367/93
5,930,199	7/1999	Wilk 367/88
6,256,263 B1	7/2001	Stevens 367/1
6,304,179 B1	10/2001	Lotito, et al. 340/545.3
6,411,202 B1	6/2002	Gal, et al. 340/425.5
6,430,988	8/2002	Watanabe73/592
2004/0140886 A1	7/2004	Cleveland 340/431

CROSS-REFERENCE TO RELATED APPLICATIONS

2004/0140886 A1 7/2004; Inventors: Ronald Cleveland and Steve Wendler; U.S. Class: 340/431.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

Not Applicable.

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC

Not Applicable.

REFERENCE TO A "MICROFICHE APPENDIX"

Not Applicable.

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to the acoustic wave methods and systems for presence or movement detection and for distance or direction finding in the case of having a plurality of ultrasound type transmitter and receiver transducers. In particular this invention refers to condition responsive early indicating systems that exploit the registration of an occasional disturbance of ultrasonic wave beams in the manner of their reflection, refraction by edge diffraction and interference by shadowing, which disturbance has been made by either an intruding subject or a trespasser.

Description of Related Art

At present there exist methods and systems of ultrasound intrusion detection in an entire volumetric surveillance areas, in which areas there are being used different arrangements of transmitting and receiving transducers, at least namely:

- fan-shaped or matrix arrangements of transmitter and receiver transducers for stationary vector directing surveillance, e.g. U.S. Patents #5,920,521 and #4,582,065 respectively;
- solitary arrangement of transmitter and receiver couples for scanning all over the surveyed area with narrow clusters of ultrasound beams, e.g. US 2004/0140886 A1; U.S. Patents #4,644,509; #5,309,144;
- multi-seat arrangement of receivers along the perimeter of protected area for detecting an occurrence of ingress or egress intrusion thru the vicinity of protected area perimeter, e.g. U.S. Patents #5,483,224 and #5,872,516;
- single-row or multi-row arrangement of transmitting and receiving transducers for realizing various processing operations with the help of reflected ultrasound beams, in particular:
 - - detection any strange subject inside the surveyed area, e.g. U.S. Patents #5,761,155, #6,411,202 B1 and #6,518,915B2;
 - - measurement of distance to intruded subjects or to the level of interface of liquid and granular materials, e.g. U.S. Patents #4,949,074, #5,231,608 and #5,131,271, #6,323,441B1 respectively;
- isolated arrangement of transmitter inside an enclosed area and positioning the receiver outside this enclosed area with the aim of detecting an occurrence of destroying the isolation of said protected area by an intruder, e.g. U.S. Patents #4,807,255, #5,638,048, #6,430,988.

As is evident from the delivered above the elucidative examples, the modern methods and systems for ultrasound intrusion detection utilize preferably the phenomenon of reflection of ultrasound beams from strange subjects that occurred inside a surveyed area. Meanwhile, it is the known fact that the process of emitting-reception of airborne ultrasound signals depends strongly upon air ambient conditions (temperature, moisture, atmospheric pressure, etc.) and therefore it is restricted spatially. In turn, this restriction predicts the limitations upon volumetric dimensions of surveyed area and consequently on the capability of earlier warning detection of either an intruding subject or a trespasser. The alternative enhancement of the entire protected space might be realized by attaching to the ultrasound-surveyed area the proper number of adjacent areas, which areas were being surveyed with use of different physical principles of intrusion detection (infrared, microwave, light level sensing, etc.), e.g. see U.S. Patents #4,857,912 and #6,127,926. Unfortunately, such a would-be method and arrangement will lead to hardware and software complexity, low reliability and great cost of an intrusion protection system as a whole. Nevertheless, it is necessary to establish such very method of intrusion protection that features with high reliability and self-defense, and meets the requirements to the multi-echelon arrangement of the protection systems of critical objects. Those strong requirements are delivered at least in the following regulations for such evidently critical objects as Nuclear Power Plants:

- Defense-in-Depth in Nuclear Safety, IAEA INSAG-10, IAEA, Vienna, 1996.
- Method for Performing Diversity and Defense-in-Depth Analysis of Reactor Protection Systems. NUREG for U.S.NRC/Prepared by G.G. Preckshot-Lawrence Livermore National Laboratory/Manuscript date: December 1994.

Furthermore, it seems to be relevant to emphasize some unique features of ultrasound that make it attractive for the purpose of faultless intrusion protection of a near field zone, namely:

- ultrasound waves are being emitted in the form of narrow directional beams and consequently do not travel around corners well, so beam patterns of the said directional beams may be easily reflected or shielded by an intruded subject; or they may be refracted, i.e. diffracted by the edge of a subject having penetrated them into small part of their peripheral lobes;
- narrow solid angle of directional reception of airborne ultrasound may be obtained with relatively small dimensions of hidden receivers;
- ultrasound is not influenced by regular “white noise” of an environment, especially by an industrial ambient, being either inside or outside.

Besides, at the present time the ultrasound processing methods and instruments are being well practiced in even multi-modular hierarchical imaging, detecting and measuring systems that contain the similar ultrasonic instrumentation and hence are reliable, convenient and low-cost. This real advancement of the processing architecture is the actual prerequisite for improving ultrasound intrusion protection technology, which the present invention is devoted to.

BRIEF SUMMARY OF THE INVENTION

With the aim of introduction into the sense and art of the novel ultrasound intrusion detection technology provided by the present invention, it is necessary to identify the new basic objects of concern, as it is set forth below.

The principle object of the present invention is to establish a method of anticipatory ultrasound intrusion detection that enables the purposeful application of all the advantageous features of ultrasound technology for sufficient enhancement of remote ability of preventive defense-in-depth ingress or egress intrusion detection throughout the near field zone and circumjacent vicinity around a surveyed critical object.

Other object of the invention is to arrange the whole protected dome-type volumetric room around a critical object in several juxtaposed areas, hence to create the multi-echelon structure in the form of multi-level solid openwork frame, outlined over the near field zone and circumjacent vicinity of a protected object regarding the remote ability of propagation of airborne ultrasound waves along their incidence and reflection trip at the forecasted atmospheric conditions of the air ambient.

Further object of the invention is to determine the geometrical shapes and dimensions of 2-D polygonal or curvilinear areas, or 3-D curved surfaces of those echelons in correspondence with the spatio-temporal parameters of air-borne ultrasound propagation and the available capabilities of selected ultrasound beam patterns to cover all the said 2-D areas or 3-D surfaces with stationary or scanning said ultrasound beam patterns. In turn, the selection of suitable beam patterns' characteristics (i.e. frequency range of a chosen transducer, effective transmitting-receiving distance of signals, solid angle of ultrasound beam pattern, rate of ultrasound attenuation, etc.) should be done with respect to the statistically forecasted conditions of ultrasound beam patterns' propagation in the air ambient around a protected object, e.g. the annual average of temperature, humidity, atmospheric pressure, cross wind flows, etc.

Another object of the invention is to compose a graphic-analytical model of intrusion vulnerability for each individual echelon, taking to consideration the real layout of protected object and the optional

models of spatio-temporal behavior of intruder or trespasser on their assumed routings, and the chosen mode of response of the emitted ultrasound signals (i.e. reflection, refraction by edge diffraction and interference by shadowing).

The other object of the invention is to choose and assign for each echelon the pertain method of ultrasound intrusion detection regarding the said mode of ultrasonic beam response, which should match the predetermined behavior of an intruding subject or a trespasser on their presumptive routings.

The further object of the invention is to compose the generalized graphic-analytical model of intrusion vulnerability for the entire protected dome-type volumetric multi-echelon structure that is being outlined in the form of multi-level solid openwork frame over the near field zone and circumjacent vicinity around a critical object. This generalized model must establish the logically correct interrelation amongst juxtaposed and even non-adjacent echelons that is destined to intrusion justification, presentation of alarm signals, and actuation the protective and defensive measures. This interrelation is based on the principle of early and preventive ultrasound detection of ingress or egress intrusion, where the said principle consists in gradual generating of caution, self-checking, intrusion vindication, and alarm and security activating signals in the result of logical processing of ultrasound signals acquired during continuous status scan of detectors in all the echelons.

Still further object of the invention is to minimize the diversity of hardware and software that should be utilized for all different ultrasound beams' response modes involved, and to compose finally the mutual set of instruments and control software algorithm for the entire defense-in-depth ultrasound intrusion detection and justification procedure. It is evident that minimized architecture of hardware should be based on the conjugation of specification figures of various ultrasound instruments, at least operating frequency and bandwidth of ultrasound emission, S/N ratio, type of signal processing domain, that are destined for practicing different beam pattern's response modes, i.e. reflection, refraction by edge diffraction, and interference by shadowing the emitted beam pattern with a target. The software apparently should represent an algorithm, which is being compiled on the basis of modeling of the intrusion event tree. This software algorithm should accomplish logical operations for presentation of the signals of intrusion detection, justification and prevention in the result of logical processing of caution and self-checking signals, acquired during continuous status scan of ultrasound detectors (i.e. receivers and transceivers) in all the echelons of the intrusion protection dome-type volumetric room.

The specific content of the invention, as well as other objects and advantages thereof, will clearly appear from the following description and accompanying figures.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

Preferred embodiments of the present invention will now be described with reference to the figures by way of illustration, in which the fundamentals of the suggested novel method of ultrasound multi-echelon intrusion detection are represented, in which like reference characters indicate like elements of method's arrangement, in which explanations of said arrangement are given, and in which:

FIG.1 shows schematically an alternative embodiment of a defense-in-depth ultrasound multi-echelon intrusion detection spatial structure in the form of multi-level solid openwork frame, outlined over the near field zone and circumjacent vicinity of a protected object, which structure provides for the enhanced remote ability of propagation of the airborne ultrasound waves. Accordingly to the present invention, this structure has been arranged in possession of juxtaposed the central (C), short-range (S) and long-range (L) areas. These areas represent the corresponding echelons of said ingress or egress ultrasound intrusion detection volumetric room. As shown at **FIG.1**, the central echelon C is being arranged inside the premises of the enclosed housing of a protected critical object 1. In this closed echelon there is being used the ultrasound intrusion detection by the stationary vector directing or space scanning techniques with reflection and refraction by edge diffraction response of ultrasound beams. The sets of transmitters and receivers are being mounted inside the premises of this object 1. According to the present invention, in the alternate embodiment of the method thereof, transmitters may be mounted inside each of the premises of the object 1, while receivers correspondingly are mounted outside these premises for detecting any breakage of their enclosures (broken walls, opened doors, windows, etc.). That case the receivers may be mounted at the peripheral outline of echelon C, where the adjacent echelon S begins.

The short-range echelon S is being shaped in the form of the 2-D polygonal or curvilinear areas, or 3-D curved surface areas at the adjoining vicinity of external peripheral outline over the buildings with said enclosed premises and over the other outdoor installations of a protected critical object. Evidently, the inner outline of echelon S is the substantial planar or volumetric solid openwork frame. In the short-range echelon S there is being used the ultrasound intrusion detection by the stationary vector directing or space scanning technique with refraction by edge diffraction response or with interference by shadowing response of ultrasound beams in the result of respectively intersection or shielding of these beams by an intruding subject or a trespasser.

At least one long-range echelon L is being arranged outwardly and adjacently to the outer peripheral outline of the short-range echelon S. In the long-range echelon L there is being used the

ultrasound intrusion detection by preferably the stationary vector directing technique with an occasional reflection response of ultrasound beams from the surface of an intruded subject.

FIG.2 shows the verifying logic matrix that represents the logical interrelation of ultrasound detection signals, acquired from different juxtaposed and non-adjacent echelons **C**, **S** and **L**. Since this logic of signals is being used for intrusion justification, the self-checking signals are being foreseen for every echelon that enables to analyze the current operating status of each echelon. The simultaneous appearance of caution and positive self-checking signals should vindicate that an intrusion has occurred in the checked echelon.

DETAILED DESCRIPTION OF THE INVENTION

The preferable embodiments of the present invention are being unveiled by the description of the innovative approach to the use of various ultrasound detection techniques and their logical interrelation that constitute the basic content of the novel Method of Defense-in-Depth Ultrasound Intrusion Detection. The following detailed description is expected to deliver the appropriate explanation to advantages of these techniques and their beneficial interaction in ultrasound early and anticipatory intrusion detection procedure.

At least one of the vital secure needs of a critical object (e.g. Nuclear Power Plant, refinery, offshore rig, flowing plant of gas-main pipeline, moored ship, plane station, helipad, etc.) is that of the reliable and stealthy intrusion protection system, see **FIG.1**. The protection reliability is to be enabled by use of early and preventive detection of an intruder or trespasser. The secrecy, in turn, may be realized thereto by utilizing ultrasound technology for detecting the presence or motion of subjects, because it is difficult to notice or suppress ultrasound waves in air without special detectors and suppressing generators respectively. The presence or motion of suspected subject within a surveyed area should result in reflection; refraction by edge diffraction or interference by shadowing of the airborne narrowly directed ultrasound beams. Keeping in mind that ultrasound attenuates in air quickly enough, it seems reasonable to arrange the whole protected room around a critical object in several juxtaposed inside and /or outside areas. These areas represent juxtaposed echelons of the entire defense-in-depth intrusion protection dome-shaped volumetric structure. The number of echelons, their shape and space dimensions depend upon the real layout of a protected object, the amount of protected volumetric room, the available spatial-temporal parameters of the airborne ultrasound propagation in forecasted conditions of the air ambient, and the predetermined behavior of an intruder or trespasser on their assumed routings.

The said expected behavior predestines correct selection of relevant ultrasonic detecting technique and instrumentation for each surveyed echelon. In compliance with the present invention the said system of the ultrasound defense-in-depth protection of the entire surveyed room must be organized in data interaction format that includes logical processing of acquired signals according to the following signal justification procedures:

- simultaneous location inside all the echelons with forming the *caution signals* in case of presence or motion of suspected subjects at least in one of the said echelons;
- keeping under surveillance the motion of suspected subjects throughout the juxtaposed and non-adjacent echelons with forming the *intrusion vindication signals*, if this motion is defined as an intrusion that threatens the protected critical object;
- forming *self-checking signals* for verification of an intrusion occurrence and current check of performance reliability of ultrasound detection facilities of every echelon;
- logically processing the *caution signals* and *intrusion vindication signals*, and presentation of the *alarm signal* as well as the necessary *security activating signals* in accordance with the designed goal function of the said ultrasound detection and protection technology of the present invention.

As it is shown at **FIG.1**, the whole room around a critical object is being arranged at least in three juxtaposed areas that are defined as central **C**, short-range **S** and long-range **L** echelons. The central echelon **C** is being arranged inside the normally enclosed at least one premise with the protected installation of a critical object **1** that optionally is placed on a supporting base **2** acting as a passive protection structure of said object from beneath. The inside reflecting surfaces **3** are being constructed to enclose normally said protected installation of object **1**. At least one pair of transmitter **4** and receiver **5** is being mounted inside the enclosed area of echelon **C**. Over the echelon **C** there is being arranged the internal border **6** of the short-range echelon **S**. The external border **7** of echelon **S** is being made to coincide with the frontier **8** of the open to outside the echelon **L**. In dependence on the real layout of a protected object **1** and hence on the physical volumetric shapes of surveyed echelons **C**, **S**, and **L** the said borders **6** and **7**, and frontier **8** are being configured like either 2-D polygonal or curvilinear, or 3-D curved spatial surfaces of a solid openwork frame, or in any combination thereof. The internal border **6** and external border **7** of the short-range echelon **S** both are being equipped with alternate pairs of the mounted opposite each other transmitters **9** and receivers **10**, so that all of the area of echelon **S** is filled in with ultrasound beam patterns **11**, which beam patterns are arranged closely and directed opposite each other. If the dimension of echelon **S** in the designed prevailing direction of

ultrasound location is bigger than the admitted value of the airborne ultrasound wave attenuation along its one-way emission trip from a transmitter to the opposite receiver, the said echelon should be divided into several sublevels. The dimension of each of said sublevel in said prevailing direction of location must provide for such admissible value of ultrasound attenuation in the forecasted conditions of the air ambient where the received signal is not less than the dead band of the ultrasonic receiver chosen for the said conditions of the air ambient. The outer surface of solid openwork frame of frontier 8 of echelon L is equipped with integrated transmitter-receiver transducers, i.e. transceivers 12, disposed in the form of preferably chequerwise lattice, so that a sort of umbrella barrage of emitted upstream ultrasound is being formed by closely adjacent beam patterns 13 where some of the transceivers 12 may be directed stationary, while another are being pivoted for scanning the solid angles that overlap each other.

The principal operational character of each echelon is based upon the chosen ultrasound detecting technique, which technique features distinctive mode of emitting of ultrasound signal and registration of its occasional disturbance regarding the expected mode of ultrasonic beam's response. Since the central echelon C represents at least one normally enclosed premise, it is reasonable to use therein the technique of ultrasound echolocation. The narrow ultrasound beam 14 is being emitted inward the enclosed area of echelon C and consequently reflected from inner surfaces 3 in the form of returned beam 15, provided these beams were not disturbed by the presence of an intruder. Otherwise, said returned beam 15 will be changed and receiver 5 consequently will register an intrusion. If the integrity of enclosure of object 1 were destroyed, see dashed lines at FIG.1 (broken walls, opened doors or hatches, etc.), the emitted beam 14 or some of the reflected beams 15 would go outward in the form of released beam 16 that might be registered by one of the receivers 10 of echelon S. In the result, an ingress or egress intrusion should be registered. Thus, inside echelon C there are being realized the couple of ultrasound techniques, namely: the ultrasound echolocation inside the enclosed premises with use of reflection of ultrasound beams; and detection of accidentally outward released the airborne ultrasound by direct receiving its beams with receivers 10. The arrangement of the said receivers 10 is being preliminary designed so that their beam patterns could overlap the areas of openings and expected damages of the enclosure of object 1. So far as echelon S is being designed for protection of proximate outside area of near field zone around the object 1, it appeared to be reasonable to use the technique of ultrasound beam interference because an expected intruder has to cross this echelon along his ingress or egress motion. In this case an intruded target 17 should interfere or shadow the ultrasound beams 11 going from transmitters 9 to receivers 10 throughout echelon S. Optionally, the

interference of an intruded target with the surveying beam patterns of echelon **S** may lead to refraction of said beam patterns by the edge diffraction phenomenon. It means that the refracted, i.e. edge diffracted ultrasound beam pattern should register the event of penetration of an intruding subject into the small part of its peripheral lobes. This small part of in-lobe penetration is less than the wavelength of airborne ultrasound emission, which is approximately of 0.3445" or 0.875 cm. at frequency of ≈ 40 kHz in normal ambient air conditions. So that, this mode of beam pattern response should provide for fast and correct detection of an intruder that tries to cross the frontiers and enter inside area of echelon **S**. At the echelon **S** there may be utilized the target detection with use techniques of unit stationary vector directing, stationary vector lattice arranging or unit/group vector scanning where selected number of receivers **10** operate in the scan mode but the rest number of receivers **10** and all the transmitters **9** operate in stationary vector directing mode. The purpose of activation of the selected group of receivers **10** for in-phase scanning is the vindication of intruder's presence inside echelon **S** and definition of vector of its motion that represents the direction and speed thereof. Since in the alternative arrangement of the present invention echelon **S** may be divided into several adjacent subechelons **S**₁, **S**₂, **S**₃, ... **S**_{n+1}, where dimensions of each echelon are limited by the distance of feasible propagation of airborne ultrasound waves in the forecasted conditions of ambient air, the remotability of ultrasound detection inside echelon **S** should be sufficiently enhanced.

The external echelon **L** is being designed for protection of circumjacent dome-type air vicinity of the layout area of the critical object **1** with the aim of early and anticipatory intrusion detection where an intruded target **18** must be found at its trajectory **19** of approaching this protected object. Since ultrasound beams **13** of echelon **L** are being emitted continuously outward the frontier **8**, and since they may return only when having been reflected from a random target in the form of reflected beams **20**, it appeared to be reasonable to apply the ultrasound beam reflection with use of stationary vector directing, stationary vector lattice arranging or unit/group vector scanning techniques where the selected number of transmitter-receiver transducers **12** may operate in stationary vector directing mode and the rest number of said transducers may operate in the volumetric scan mode. The solid openwork frames of echelons **S** and **L** may be designed for 2-D polygonal or curvilinear, or 3-D curved surface array arrangement of pairs of transducers **9** and receivers **10** (echelon **S**), and of transmitter-receiver transducers **12** (echelon **L**) in dependence on the layout and enveloping space shape of the protected buildings and outdoor installation of the object **1**. The purposeful choice of one of said techniques of ultrasound emitting-receiving and said arrangement of transmitter-receiver transducers **12** are being done in dependence on the preliminary assumed graphic-analytical model of intrusion vulnerability of

the long-range echelon **L**. Since the behavior of target **18** inside echelon **L** is really crucial for all the consequent intrusion protection activity, there is being organized the estimation of the main parameters of said behavior. For example, the analysis of the changes of dimension **H** and speed of an approaching subject in time and value, see **FIG.1**, may run the assessment of the threatening approach of target **18** to a protected object **1** or may indicate the invulnerable passing by of the said subject. Optionally, Doppler effect may be used for intrusion detection and signal processing inside area of the long-range echelon **L**.

The verifying logical matrix, shown at **FIG.2**, enables to organize the systematized programmable analysis of the directional sequence of retrieved signals and to assess direction, intensity and at last the real security threat of intrusion to the buildings, works and installations of a protected object **1**. This analysis of real security menace is being accomplished with respect to the preliminary composed the local echelons' graphic-analytical models of predictive vulnerability for each of the echelons and the generalized graphic-analytical model of the presumptive intrusion vulnerability for all the multi-echelon protective structure. Each of the local echelon's graphic-analytical models is being composed in accordance with the real layout of the protected echelon and presumptive spatio-temporal behavior of an intruder, and with the ultrasound detecting technique of emission-response, chosen for each echelon **C**, **S** and **L**. If to say rather more detailed, the working-out of the graphic-analytical model of intrusion vulnerability for each echelon is being accomplished with regard to the supposed options of spatio-temporal purposeful behavior of intruder or trespasser along their possible routings inside premises of the central echelon **C**, around buildings and works of short-range echelon **S**, within reach of ultrasound location inside the space of the long-range echelon **L**. The said options of ingress or egress routings of intruder or trespasser thru every echelon are also being searched with taking to account the layout and architectural features of the available protective barriers against an intrusion, and various assumed ways of the trespassers' accessibility to the critical works and installations therein. The results of search of the said options are being used for verification of geometrical shape of every echelon by comparison of spatio-temporal parameters of intruder's or trespasser's purposeful behavior with spatio-temporal parameters of ultrasound beams' propagation and signaling response in prevailing directions of location. Then the echelons' logical equations are being set up in advance to reveal the factors of menaces inside the echelons and sublevels therein based on the said graphic-analytical models of intrusion vulnerability that consists in the failure probability of protected facilities. This vulnerability should be increased for facilities, which belong to some sublevels inside one echelon or to different echelons at the same time.

The generalized graphic-analytical model is being compiled with taking to consideration the specificity of each local echelon's model and the software-programmable inter-echelon informational and processing logical interaction among sublevels of each echelon and among juxtaposed and non-adjacent echelons. See **FIG.2** that illustrates the inter-echelon tracing of an intruding subject or a trespasser. The said generalized graphic-analytical model is being prepared, including the steps of:

- designation of available physical barriers for having used them as hindrances to access the critical installations and as entrapments along the presumed routings of an intruding subject or a trespasser where this designation is being fulfilled regarding the previously simulated model of the presumptive spatio-temporal behavior of an intruding subject or a trespasser; and
- definition of the territorial contours and limits of operating time, violation of which with the non-authorized presence or movement of an intruded subject or a trespasser should be considered as the actual hazardous intrusion; and
- plotting the intrusion event tree in the form of graphic representation or table matrices which identify the interrelations of sublevels inside any echelon, and among juxtaposed or non-adjacent echelons that are based on the sequence of the cause-effect events of registration of an intrusion occurrence and definition of the vulnerability and menaces due to the presence and motion of an intruded subject or trespasser; and
- accomplishment of the graphic presentation of intrusion event tree on the floor plans of enclosed premises of echelon C and on the lay-out of the near field zone of echelon S for detection of intrusion cause-effect cross-linkages and respective facts of intrusion menaces among sublevels inside echelons, and among juxtaposed and non-adjacent echelons C, S and L; and further
- setting up the generalized graphic-analytical model itself in the form of graphic-analytical representation of inter-echelon dependable vulnerability at occurrence of one or a few intrusions in one of the echelons, or in some of them simultaneously.

So that, the generalized graphic-analytical model and verifying logical matrix, see **FIG.2**, are being used for prediction of the variable vector of the assumed intruder's threatening motion throughout the echelons and for programming the logically motivated sequential presentation of the caution, self-checking, intrusion vindication signals, and final signals of alarm and starting the passive and active measures of protection and defense. The presentation of final signals of alarm and starting the said security measures is the goal function of the new method of ultrasound intrusion detection.

The inter-echelon informational and processing logical relation is being treated and handled by the logical decision matrix, which is the constituent of the control software algorithm. The said logical decision matrix is being designed by placing top-down into the main column all the sublevels of the echelons and entire echelons in the order of defense-in-depth structure, beginning from echelon **L**, and further by arranging all factors of menaces, drawn from the said echelons' logical equations, in the rows against the respective echelons' sublevels and entire echelons in the order of the diminishing rate of said factors of menaces.

The generalized resolving logical equation is being set up in the result of the analysis of logical decision matrix and generalized graphic-analytical model of the intrusion vulnerability with regard to an intrusion cause-effect cross-linkages among sublevels inside echelons, and among juxtaposed and non-adjacent echelons **C**, **S** and **L**.

The goal function of ultrasound intrusion detection is being resolved during continuous status scan and data acquisition in the steps of:

- solving the echelons' logical equations for justification the fact of intrusion menace; and
- carrying out running analysis of acquired facts of intrusion menaces by logical decision matrix, and
- processing the generalized resolving logical equation by the said control software algorithm with respect to the said verifying logical matrix.

According to the present invention the informational and processing logical interrelation among either juxtaposed or non-adjacent echelons **L**, **S** and **C** is being treated and handled by the logical decision matrix of the said control software algorithm, which algorithm operates the continuous status scan of all the ultrasonic transceivers and oppositely aligned pairs of transmitters and receivers in every echelon simultaneously, and which algorithm provides for:

- transferring the acquired data of continuous status scan to the said system of echelons' logical equations, verifying logical matrix, and logical decision matrix;
- ability of the resolver, governed by the said soft ware algorithm, to process the acquired data by the said echelons' logical equations, verifying logical matrix, logical decision matrix and generalized resolving logical equation up to the logically correct decision of the goal function of the intrusion detection and protection method;
- creation and presentation of logically true sequence of the caution and self-checking signals for every intrusion-suspected echelon, see **FIG.2**, signal of intrusion vindication for the really affected echelon, and final signals of alarm and actuation of security measures where the

creation and presentation of the said final signals is the goal function of the new method of ultrasound intrusion detection;

- generation of signals of starting said security measures of active and passive protection and defense which measures include at least: activation of the alarm system, enclosing the physical barriers around the protected works and installations, hence entrapping a trespasser on its actual routing preferably inside echelon **C**, application of disabling tear gas, involving the guard troops, deploying inflatable air obstacles in echelons **S** and **L** or opening the defensive fire therein.

The instrumentation of ultrasound intrusion detection and protection system should consist of at least:

- the resolver, which handles the system of said echelons' logical equations, verifying logical matrix, logical decision matrix of inter-echelon factors of menaces, and generalized resolving logical equation;
- data control block that operates the ultrasound location modes and data acquisition procedure; and
- system control block that forms and presents the signals of intrusion detection, justification and prevention.

The architectural design of ultrasound processing hardware is being determined basically by use of different ultrasound intrusion detection techniques in each echelon. These techniques are based on the different modes of ultrasound signals' responses (i.e. reflection, refraction by edge diffraction and interference by shadowing). The said architectural design is being additionally defined by the chosen modes of intrusion monitoring inside every echelon with stationary vectoring or continuous scanning of all the ultrasonic receivers, by optional utilization of Doppler detection technique, and by customized use of the automatic adjustment of emitting-receiving frequency regarding running changes in the ambient air conditions. Thus, there is the evident necessity to minimize the diversity of all hardware and software being utilized in echelons **C**, **S** and **L** in assortment and power consumption. The said minimization is suggested done in the steps of:

- graphical matching of frontiers of juxtaposed echelons for elimination of dead spots of ultrasound detection, and graphical prototyping of overlapping the protected areas of echelons **C**, **S** and **L** completely with beam patterns of chosen transceivers, transducers and receivers ; and
- conjugation of specification figures of various ultrasound instruments involved, at least such as operating frequency and bandwidth of ultrasound emission, S/N ratio, and type of signal processing

domain, which specification figures are destined for practicing different modes of response of ultrasound beam patterns, including reflection, refraction by edge diffraction, and interference with shadowing the emitted beam pattern by a target; and

- unification of instrumentation for different modes of intrusion monitoring inside every echelon with stationary vectoring or continuous scanning of all the ultrasonic receivers, for the optional utilization of Doppler detection technique, and for technique of the automatic emitting-receiving frequency adjustment under running changes in the ambient air conditions.

The aim of the innovative approach of the present invention is to enhance the remotability of ultrasound intrusion monitoring due to the multi-level arrangement of ultrasound surveying network of transducers and receivers that enables long-range ultrasound location in spite of its intensive attenuation in the ambient air. It permits to meet the requirements of functional diversity and operational reliability in various redundant trains of reliable defense-in-depth safety systems.

Therefore, the method and arrangement of effective and stealthy ultrasound intrusion detection according to the present invention are of the evident necessity for protection of Nuclear Power Plants, refineries, offshore rigs, flowing plants of gas-main pipeline, and other civilian and military objects that feature complex spatial component layout.

The present invention is not to be confined to the precise details herein shown and described, nevertheless changes and modifications may be made so far as such changes and modifications indicate no significant deviation from the sense and art of the claims attached hereto.